

Oracle
1Z0-070
Oracle Exadata X5 Administration



QUESTION & ANSWERS

Version: 8.0

Question: 1

Batch and DSS workloads in your Exadata X6 Database Machine are causing performance problems for OLTP workloads at certain times of the day.

There are five RAC databases performing OLTP I/O. Two of them also perform batch I/O. There is another RAC database that performs only DSS I/O.

You are asked to resolve this problem so that the OLTP workload will not suffer when competing with the batch or DSS workloads.

You decide to use the I/O resource manager.

Which is the best way to solve this problem?

- A. Create a category plan with EXADCLI calling EXACLI to give the OLTP category the highest priority in all the cells, and use the Database Resource Manager to create the OLTP category and map all OLTP- oriented consumer groups in all databases to it.
- B. Use the Database Resource Manager to give the OLTP category the highest priority and use EXADCLI calling EXACLI to create the OLTP category in all the cells.
- C. Create a category plan with EXADCLI calling EXACLI to give the OLTP category the highest priority in all the cells, and use the Database Resource Manager to give the OLTP consumer group the highest priority in all databases.
- D. Create a database plan using EXADCLI calling EXACLI to give OLTP I/O the highest priority from all six databases.

Answer: C

Explanation:

You can manage I/O resources based on categories by creating a category plan.

You can add any number of categories, or modify the predefined categories. You should map consumer groups to the appropriate category for all databases that use the same cell storage. Any consumer group without an explicitly specified category defaults to the OTHER category.

References:

<http://docs.oracle.com/cd/EE0020001/SAUA/exadata-storage-series-irm.htm>

Question: 2

Identify three valid reasons for creating multiple grid disks in a single hard disk-based cell disk.

- A. to implement storage realms so that storage that can be reserved for specific resource consumer groups in the same database
- B. to enable the creation of normal or high redundancy ASM disk groups
- C. to segregate storage into multiple pools with different performance characteristics
- D. to enable disk mirroring for the system area
- E. to implement storage realms so that storage can be reserved for specific databases

F. to implement storage realms so that storage that can be reserved for specific Oracle Infrastructure

Answer: B,C,F

Explanation:

Creating multiple grid disks per cell disk allows you to create multiple pools of storage in the same Exadata Storage Server. The multiple grid disks can be assigned to separate ASM disk groups, which can be provisioned to different databases.

Note: Grid disk is a logical disk that can be created in a cell disk. In a standard Exadata deployment we create grid disks in hard disk based cell disks only. While it is possible to create grid disks in flash disks, this is not a standard practice.

F: After you complete the cell configuration, you can perform the following optional steps in the storage cell:

References:

<https://docs.oracle.com/cd/EE0020001/SAUA/SAUA.pdf>

Question: 3

Which three statements are true concerning the configuration of SNMP in an Exadata X5 or X6 Database Machine?

- A. All SNMP notifications from the storage server ILOMs are sent directly to the Automatic Service Request (ASR) manager.
- B. Some SNMP notifications may be configured using the alter cell command in the storage servers.
- C. The Database Machine internal Cisco Switch communicates directly with the Enterprise Manager agent via SNMP.
- D. Some SNMP notifications from a storage server ILOM are sent directly to the management server (MS) process in the same storage servers.
- E. All SNMP notifications from a database server ILOM are sent directly to the Automatic Service Request (ASR) manager.
- F. All SNMP notifications from a database server ILOM are sent directly to the management server (MS) process in the same database server.

Answer: B,D,E

Explanation:

B: You can configure SNMP Trap Destinations for the Exadata Storage Servers with the following command:

```
# cellcli -e "alter cell sompSubscriber=(host='ASR-Manager-Oracle-IP-address',port=162,community=public,type=asr)"
```

D: Exadata Storage Server plug-io

This extends the monitoring of Exadata cells in addition to providing a GUI interface. The plug-io uses an SSH connection to the cell monitor user in the cells and uses list commands only. This is for interactive monitoring. One may also set thresholds using the plug-io which are distinct from any thresholds set using cellcli utility as the celladm user. For alerts to be sent to the plug-io, SNMP traps are used as follows:

Cell ILOM alerts are sent to the cell Management Server (MS) via an SNMP trap. The MS then sends

SNMP notifications toward the plug-io.

Cell alerts flagged by MS itself, such as cell thresholds being exceeded, or ADR software alerts, are sent to the plug-io using SNMP.

E: Database Server ILOM plug-io

Monitoring databases and their instances, ASM environments, the AFD infrastructure, and the host software environment are done by Enterprise Manager in the usual way as these are standard targets. But monitoring the hardware for the database servers requires the ILOM plug-io, as there is no Management Server (MS) in the database servers to receive SNMP traps from the ILOM. The plug-io will receive sensor state and availability data from the ILOM including alerts based on pre-set ILOM thresholds.

References:

<https://dbatrain.wordpress.com/2011/06/>

<http://docs.oracle.com/cd/E21650001/html/E21660//40015671004046500.html>

Question: 4

You have partitioned an X5-2 full rack into two four-node RAC clusters called CLUSA and CLUSB.

Network is used and the storage grid has not been partitioned.

Which two set of files in which servers must be modified after completion of Exadata storage expansion rack to your X5-2 Exadata Database Machine in the fabric so that the storage servers in the expansion rack are added to the storage grid?

- A. the CELLINIT.ORA files in the database servers in CLUSA
- B. the CELLIP.ORA files in the database servers in CLUSA
- C. the CELLINIT.ORA files in the database servers in CLUSB
- D. the CELLIP.ORA files in all existing Exadata storage servers
- E. the CELLIP.ORA files in the database servers in CLUSB
- F. the CELLIP.ORA files in all newly added Exadata storage servers

Answer: B,E

Explanation:

The cellip.ora is the configuration file, in every compute node (database server), that tells ASM instances which cells are available to this cluster.

The cellip.ora file contains the storage cell IP addresses.

References:

<http://docs.oracle.com/cd/EE0020001/SAAUA/exadata-storage-server-configuration.htm#SAAUA20360>

Question: 5

You plan to monitor the status of the motherboard, memory, power, fans, and network cards in the database nodes in your Exadata X6 Database Machine using Enterprise Manager.

Where must you set the thresholds for these hardware components and why, to ensure that sensor readings, faults, and any related alerts, are visible in Enterprise Manager?

- A. No thresholds need to be set because they are present in the ILOM and in Enterprise Manager.

- B. Set thresholds in ILOM and in Enterprise Manager because they are not preset anywhere and must be set in both places.
- C. Set thresholds only in ILOM because they are not preset anywhere but need to be set only in ILOM.
- D. No thresholds need to be set because they are preset in the ILOM and these are sufficient for monitoring.

Answer: D

Question: 6

Examine this list of software components:

1. Oracle Virtual Machine (OVM)
2. Oracle Enterprise Manager Agent (OMA)
3. ASM instance
4. RDBMS instance
5. Automatic Diagnostic Repository Component Interpreter (ADRCI)
6. CELLCLI
7. Cell Server (CELLSRV)
- E. diskmon

Identify the location where these software components can run in the standard Exadata Database Machine deployment.

- A. 1, 2, 3 and 4 run in the database servers; 5, 6, 7, and E run in the Exadata storage servers.
- B. 1, 2, 3, 4, 5, and E run in the database servers; 5, 6, and 7 run in the Exadata storage servers.
- C. 1, 2, 3, 4 and E run in the database servers; 5, 6, and 7 run in the Exadata storage servers.
- D. 3, 4 and E run in the database servers; 1, 2, 5, 6 and 7 run in the Exadata storage servers.
- E. 2, 3, 4 and E run in the database servers; 1, 5, 6 and 7 run in the Exadata storage servers.

Answer: B

Explanation:

Automatic Diagnostic Repository Component Interpreter (ADRCI) can be used in an Exadata storage server.

Question: 7

Which two statements are true regarding the use of Auto Service Request (ASR) with an X6 Database Machine?

- A. The database server ILOMs must use SMTP prior to the management network for notifications to ASR Manager.
- B. The database server ILOMs must have SNMP traps configured to use the management network for notifications to ASR Manager.
- C. The storage server ILOMs must have SNMP traps configured to use the management network for notifications to ASR Manager.
- D. The database server MS process must have SNMP traps configured to use the management

network for configurations in ASR Manager.

Answer: B,C

Explanation:

B: Database Server ILOM plug-in

Monitoring databases and their instances, ASM environments, the Grid Infrastructure, and the host software environment are done by Enterprise Manager in the usual way as these are standard targets. But monitoring the hardware for the database servers requires the ILOM plug-in, as there is only Management Server (MS) in the database servers that receive SNMP traps from the ILOM. The plug-in will receive sensor state and availability data from the ILOM including alerts based on pre-set ILOM thresholds.

C: Exadata Storage Server plug-in extends the monitoring of exadata cells in addition to providing a GUI interface. The plug-in uses an SSH connection to the cell monitor user in the cells and uses list commands only. This is for interactive monitoring. One may also set thresholds using the plug-in which are distinct from any thresholds set using cellcli utility as the celladm user. For alerts that are sent to the plug-in, SNMP traps are used as follows:

Cell ILOM alerts are sent to the cell Management Server (MS) via an SNMP trap. The MS then sends SNMP notifications toward the plug-in.

Cell alerts flagged by MS itself, such as cell thresholds being exceeded, or ADR software alerts, are sent to the plug-in using SNMP.

References:

<https://dbatraio.wordpress.com/2011/06/>

<http://docs.oracle.com/cd/E21650001/html/E21660//40015671004046500.html>

Question: 8

Which three statements are true regarding the configuration of Auto Service Request (ASR) in an X5 Database Machine?

- A. ASR Manager may be installed in any type of server running Oracle Solaris.
- B. ASR Manager may be installed in any type of server running Oracle Linux.
- C. Oracle Linux must be used in the server where ASR Manager is installed.
- D. SMTP must be enabled in at least one database server.
- E. Oracle Solaris must be used in the server where ASR Manager is installed.
- F. ASR Manager must be installed in one of the database servers.
- A. HTTPS connectivity must be enabled from the ASR Manager host to the Internet.

Answer: A,B,G

Explanation:

AB: Oracle recommends that you install Oracle ASR Manager in an external, standalone server. This server receives fault telemetry information from Oracle Exadata Database Machine servers. This server must run on Oracle Solaris or Linux operating system.

A: Before installing Oracle Auto Service Request (Oracle ASR) you must ensure connectivity to the Internet using HTTPS.

References:

Oracle Auti Service Request Exadata Database Machine Quick Installation Guide
http://docs.oracle.com/cd/EE0020001/ASXQI/tic.htm#AUID-E0102315-1B1A-4B5A-E0BB-04BB5B6ABB05

Question: 9

Which three storage components are available after a virtualized standard deployment of an X5 Database Machine using high-capacity disks?

- A. mirrored system area on hard disk 0, hard disk 1, and hard disk 2
- B. Exadata Smart Flash Cache using all of the flashdisk space
- C. the DBFS0DA diskgroup with high redundancy
- D. mirrored system area on hard disk 0 and hard disk 1
- E. the RECO<DBM0Name> ASM diskgroup
- F. the DATA0<DBM0Name> ASM diskgroup

Answer: C,E,F

Explanation:

The first two disks of Exadata Storage Server are system disks. Oracle Exadata Storage Server Software system software resides on a partition of each of the system disks. These partitions on both system disks are referred to as the system area.

The default configuration of Exadata is to have 3 diskgroups - DATA, RECO, and DBFS0DA.