



Visit and Download Full Version Certificationtime Exam Dumps
<https://certificationtime.com/updated/350-501-exam-dumps-pdf/>



Cisco

Exam Questions 350-501

Implementing and Operating Cisco Service Provider Network
Core Technologies

<https://certificationtime.com/>





QUESTION 1

Refer to the exhibit. Router 1 was experiencing a DDoS attack that was traced to interface gigabitethernet0/1. Which statement about this configuration is true?

- A. Router 1 accepts all traffic that ingresses and egresses interface gigabitethernet0/1.
- B. Router 1 drops all traffic that ingresses interface gigabitethernet0/1 that has a FIB entry that exits a different interface.
- C. Router 1 accepts source addresses that have a match in the FIB that indicates it is reachable through a real interface.
- D. Router 1 accepts source addresses on interface gigabitethernet0/1 that are private addresses.

Answer: C

QUESTION 2

Which configuration enables BGP FlowSpec client function and installation of policies on all local interfaces?

- A. flowspec address- family ipv4 local-install interface-all
- B. flowspec address- family ipv4 install interface-all local
- C. flowspec address- family ipv4 install interface-all
- D. flowspec address- family ipv4 local-install all-interface

Answer: A

QUESTION 3

Welcome to download the Newest CertificationsTime 350-501 dumps

<https://certificationstime.com/updated/350-501-exam-dumps-pdf/>

Refer to the exhibit. A network engineer is configuring customer edge routers to finalize a L2VPN over MPLS deployment. Assume that the AToM L2VPN service that connects the two CEs is configured correctly on the service provider network.

Which action causes the solution to fail?

- A. OSPF does not work with L2VPN services.
- B. The routing protocol network types are not compatible.
- C. A loopback with a /32 IP address has not been used.
- D. The xconnect statement has not been defined.

Answer: B

QUESTION 4

Which task must be performed first to implement BFD in an IS-IS environment?

- A. Configure BFD in an interface configuration mode.
- B. Disable Cisco Express Forwarding on all interfaces running routing protocols other than IS-IS.
- C. Configure all IS-IS routers as Level 2 devices.

Welcome to download the Newest CertificationsTime 350-501 dumps

<https://certificationstime.com/updated/350-501-exam-dumps-pdf/>

- D. Configure BFD under the IS-IS process.

Answer: D

QUESTION 5

A customer of an ISP requests support to setup a BGP routing policy. Which BGP attribute should be configured to choose specific BGP speakers as preferred points for the customer AS?

- A. lowest multi-exit discriminator
- B. highest local preference outbound
- C. lowest local preference inbound
- D. highest local preference inbound

Answer: B

QUESTION 6

Welcome to download the Newest CertificationsTime 350-501 dumps

<https://certificationstime.com/updated/350-501-exam-dumps-pdf/>

Refer to the exhibit. Which two statements about the IS-IS topology are true? (Choose two.)

- A. R1 and R4 are Level 2 neighbors.
- B. All four routers are operating as Level 1-2 routers.
- C. All four routers are operating as Level 2 routers only.



- D. All four routers are operating as Level 1 routers only.
- E. R1 and R2 are Level 2 neighbors.

Answer: AB

QUESTION 7

Refer to the exhibits. R1 and R2 are directly connected and IS-IS routing has been enabled between R1 and R2. R1 generates the above log message periodically. Based on this output, which statement is true?

- A. IS-IS neighbor authentication is failing for Level 2 PDUs only.
- B. IS-IS neighbor authentication is failing for Level 2 first and then for Level 1 PDUs.
- C. IS-IS neighbor authentication is failing for Level 1 and Level 2 PDUs.
- D. IS-IS neighbor authentication is failing for Level 1 PDUs only.

Answer: D

Full Access

<https://certificationtime.com/updated/350-501-exam-dumps-pdf/>