




Exam Questions 600-455

UCCED Designing Cisco Unified Contact Center Enterprise

https://certificationstime.com/





QUESTION 1

With Cisco Unified Contact Center Enterprise, what is the maximum number of skill groups in a Cisco Finesse Queue gadget?

A. 100

B. 15

C. 50

D. 20

Correct Answer: C

QUESTION 2

Which option describes the impact of co-loading the Cisco Unified Outbound SIP Dialer on the same servers as the agent peripheral gateway in the Cisco Unified Contact Center Enterprise?

- A. Cisco Unified Outbound Dialer does not reduce agent capacity on the peripheral gateway server.
- B. Cisco Unified Outbound Dialer reduces agent capacity by a factor of four--each outbound port is equivalent to four agents on the peripheral gateway.
- C. Cisco Unified Outbound Dialer reduces agent capacity by a factor of 1.33--each outbound port is equivalent to 1.33 agents on the peripheral gateway.
- D. Cisco Unified Outbound Dialer reduces agent capacity by a factor of 15--each outbound port is equivalent to 15 agents on the peripheral gateway.

Correct Answer: C

QUESTION 3

Which type of MTP is supported with Cisco Unified Mobile Agent?

- A. MTP Pass-Through
- B. MTP No Pass-Through
- C. MTP Pass-Around
- D. MTP No Pass-Around

Correct Answer: B

QUESTION 4

Erlang calculations are used to size contact center resources. Which two resources are sized by using Erlang-B? (Choose two.)

- A. agents
- B. IVR ports
- C. PSTN gateway trunks
- D. reporting ports
- E. estimated wait

Correct Answer: BC

QUESTION 5

The Cisco Finesse supervisor features extend the agent desktop with additional gadgets. Which three additional features are provided? (Choose three.)

- A. team performance gadget to view agent status
- B. queue statistics gadget to view queue (skill group) statistics for the supervisor\\'s queues
- C. Cisco Unified Communications Manager Remote Silent Monitoring
- D. barge-in and intercept
- E. gadget to park calls
- F. transcoder gadget for recording

Correct Answer: ABD

QUESTION 6



Which three statements about the high availability of Cisco Unified Intelligent Contact Management central controller are valid? (Choose three.)

A. If one ICM call router of a duplex pair of Cisco Unified ICM call routers fails, the surviving ICM call router recognizes the failure when it receives no response to heartbeats over the private LAN.

- B. During Cisco Unified ICM call router failover processing, calls in progress in Cisco Unified Customer Voice Portal are disconnected, but all new calls are processed successfully.
- C. If ICM Logger side A fails, the impact of call processing is limited to ICM call router side

D.

- E. If ICM Logger side A fails, router side B cannot send historical info to ICM Logger side A and is limited to ICM Logger side B.
- F. There is no impact on call processing during a Cisco Unified ICM Logger failure.
- G. If the private LAN fails, the peripheral gateways are used to help determine the active call router side of the duplex pair.
- H. If ICM Logger side B fails, the ICM Router side B cannot send real-time and historical info to logger side A.

Correct Answer: AEF

QUESTION 7

How does the Cisco Unified Contact Center Enterprise solution encrypt the logger database?

A. AES

B. SHA

C. MD5

D. TLS

Correct Answer: C

QUESTION 8

Which three WAN/MAN configurations are valid in the Cisco Unified Contact Center Enterprise clustering over the WAN deployment model? (Choose three.)

- A. A highly available visible network WAN/MAN/DWDM and a dedicated private network WAN.
- B. A highly available MPLS WAN shared by the visible and private networks with a 2 second convergence time.
- C. A highly available MPLS WAN shared by the visible and private networks where the private network is pinned to a single path and the visible network aligned to an alternate path failing to the private network path as redundant link with QoS and bandwidth provisioning.
- D. A highly available DWDM/CWDM network shared by the visible and private networks with a sub-500 ms convergence time.
- E. All traffic is converged on a single MPLS network by using appropriate QoS markings and settings to ensure latency and bandwidth requirements.
- F. A highly available DWDM/CWDM network shared by the visible and private networks with 1500 ms convergence

Correct Answer: ACD

Full Access

https://certificationstime.com/updated/600-455-exam-dumps-pdf/